

Transformer type	Input voltage	Input current [A]	Power range [W]	Output voltage [V]	Power factor	Ambient temperature [°C]	Insulation class	Number of input terminals	Number of output terminals	Casing tightness class	weight [g]	Casing type	Dimensions AxBxC
YT 50	230V ±10% 50Hz	0,22	0-50	11,5	0,99	0-40	II	2x0,5mm2	1mm2	IPX7	75	EC 05	71,5 x 35 x 23,4
YT 60		0,27	0-60					2x0,5mm2	1mm2	IPX7	75	EC 05	71,5 x 35 x 23,4
YT 60 RF		0,27	0-60					2	2	IP44	95		188 x 34,2 x 36,5
YT 70		0,33	0-70					2	2	IP40	115	EC 10	118 x 36,5 x 29,5
YT 105		0,46	0-105					2	4	IP40	120	EC 10	118 x 36,5 x 29,5
YT 150		0,65	0-150					4	6	IP40	235	EC 20	173 x 54 x 33
YT 210		0,93	0-210					4	6	IP40	285	EC 30	173 x 54 x 38
YT 250		1,1	0-250					4	6	IP40	285	EC 30	173 x 54 x 38
YT 70	230V ±10% 50Hz	0,35	0-70	24	0,99	0-40	II	2	2	IP40	115	EC 10	118 x 36,5 x 29,5
YT 150		0,65	0-150					4	6	IP40	235	EC 20	173 x 54 x 33

Casing dimensions

